

WL250

Clean and refreshing water on demand.

The WL250 delivers on a promise of endless refreshing chilled water for your workplace. It features multi-stage filtration and ultraviolet light sanitization to reduce bacterial growth and prevent potential biofilm buildup. The business friendly design and guaranteed reliability ensure you have all the quality cold and hot water your employees and guests need.



Advanced Technology

The WL250 has three core technologies:



High Performance Filtration

This model can be configured with four stage reverse osmosis filtration or multi-stage carbon filtration depending on water conditions. These processes remove water contaminants and chlorine to improve water taste and odor.



In-tank UV

An in-tank ultraviolet light reduces bacterial growth to guarantee fresh clean water.



BioCote® Anti-Microbial Protection

Antimicrobial technology that is proven to be effective against a wide range of microbes such as odor causing and staining bacteria, mold and fungus. BioCote reduces microbes by up to 99.99%

*For more information visit www.biocote.com/home-us.

Good for the Earth

Waterlogic coolers have been shown to reduce carbon footprint by up to 72% compared to bottled water coolers.*

Bottleless water coolers reduce plastic bottle contribution to landfills.

The WL250 is ENERGY STAR certified.



*Waterlogic 2014 www.waterlogic.com/benefits/simple-green/carbon-reduction-label

WL250 Features

- Unlimited cold and hot filtered water on demand
- UV technology to reduce bacterial growth
- BPA Free and better for the environment
- Recessed faucet to prevent contamination
- BioCote antimicrobial protection to reduce the spread of germs
- Easy connection to your existing water supply
- Option for drip tray drainage
- Tower and countertop models to fit all environments



Water Options	Technical Features	
 Cold water  Hot water	Type available	Tower Countertop
	Tower dimensions	13.5" (W) x 40.5" (H) x 14.5" (D) 343 mm x 1029mm x 368mm
	Counter top dimensions	13.5" (W) x 17.75" (H) x 14.5" (D) 343mm x 451mm x 368mm
	Compressor	120V/60Hz
	Dispense area height	8.5in (216mm)
	Weight	Tower: 58lbs (26.3kg) Countertop: 42lbs (19.1kg)
	Recommended filtration	Countertop: Carbon Block (CBC) 1 micron with lead and cyst reduction Tower: Sediment Block, Carbon Block (CBC), Granular Activated Carbon (GAC)
	Additional features	Mode Indicator Leak Detection *CT only
	Capacity	Hot tank: 1.5 liters Cold tank: 4 liters tower 2 liters counter top
Water temperatures	Cold: 40°F Hot: 188°F	

02-111501

Tested and Certified



CE QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLT Trading Ltd (Company with licence is WLI (Trading) Limited) is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

Waterlogic USA
11710 Stonegate Circle
Omaha, NE 68164

Tel: 402.905.2001

info@waterlogicusa.com
www.waterlogicusa.com